



MANUFACTURERS AND DEALERS OF SPECIALITY CHEMICALS & AUXILIARIES

SURVEY NO 38, PLOT NO-3, NEAR SHIVRAM DYEING AND PRINTING MILL, OPP JC ENGINEERING, KADIWALA STREET, KHATODARA SURAT-395002
MOBILE NO 9825113647

EMAIL- Info@harshchemicals.com

WEBSITE- www.harshchemicals.com

HARSHOL ECO CARRIER

Harshol ECO Carrier is multifunctional leveling agent as well as ecofriendly Carrier which also gives blooming effect {tone developing}. This is a specially developed polymer technology dyeing carrier.

Specifications

composition: Blend of Polymers and Polyether's

Appearance: Clear liquid

Nature: Nonionic

Compatible with all ionic natures

Application

- For low temperature dyeing **Harshol ECO Carrier** is recommended **2gpl** with required acid and leveling agent in dye bath . Dyeing is to be carried at **105°C for 60 minutes** , drain the bath and do RC if required .
- For regular dyeing **Harshol ECO Carrier** is recommended **1gpl** in the dye bath with required acid and leveling agent
- For printing **Harshol ECO carrier** is recommended 2% is added in printing paste with acid and loop accelerator.
- For blooming effect {Tone Developer} **4.5%**of **Harshol ECO carrier** is recommended with finish chemicals.

Note:

The information and recommendation presented hereby complied with utmost care. But they cannot be extended to cover every possible case. They are intended only to serve as non-binding guidelines and may not be adapted to prevailing conditions.

Precautions:

- Keep the container closed while not in use.
- keep container in cool shade.
- Do not expose the material to direct sun light.
- Follow routine safety precautions and exercise good housekeeping.

Disclaimer:

The product incorporated and sold is without warranty expressed or implied. Including warranty of merchantability and fitness of use of this material and condition that purchaser shall make their own tests to determine the suitability and the quality of the product for their particular purpose. The user assumes all risks of use and handling, whether or not in accordance with any statement of the supplier. Supplier's liability if any, for any action arising out of the material being supplied shall be limited to only replacement of material.