

Harshol-Super Drum

Powerful wetting, rewetting and swelling agent.

Harshol-Super Drum is a very powerful concentrated APEO Free wetting ,rewetting and swelling agents to reduce hold time of drumming.

Specifications:

Composition:	Di-Alkyle Aliphatic Alcohol Ethoxylate
Appearance:	Clear colourless liquid
Nature:	Anionic/Non-ionic
pH:	Neutral
Solubility:	Soluble in water in all proportions
Compatibility:	Compatible with anionic, non-ionic and cationic
Biodegradability:	Good

Advantages:

- Powerful swelling agent for all type of textile materials.
- It works as an effective swelling agent in het dyeing machine.
- it is biodegradable

Application:

For Drumming

Generally after grey wash with desires alkali and 0.25% non ionic detergent at 80°C for 20 minutes 0.75% to 1.0% of Harshol-super drum is suggested at 125°C to 130°C for 30 to 40 minutes.

For Jet Dyeing process:

Generally after grey wash with desires alkali and 0.25% non ionic detergent, 1% Harshol-super Drum is suggested with required alkali for weight reduction at 125°C to 130°C for 60 to 90 minutes to get the desired grainy effect.

Note:

The information and recommendation presented hereby complied with utmost care. But they cannot be extended to cover every possible case. They are intended only to serve as non-binding guidelines and may not be adapted to prevailing conditions.

Precautions:

- Keep the container closed while not in use.
- keep container in cool shade.
- Do not expose the material to direct sun light.
- Follow routine safety precautions and exercise good housekeeping.

Disclaimer:

The product incorporated and sold is without warranty expressed or implied. including warranty of merchantability and fitness of use of this material and condition that purchaser shall make their own tests to determine the suitability and the quality of the product for their particular purpose. The user assumes all risks of use and handling, whether or not in accordance with any statement of the supplier. Supplier's liability if any, for any action arising out of the material being supplied shall be limited to only replacement of material.